



PRODUCTION LINE – TECHNICAL FEATURES	
PRODUCTION SPEED	20 meter/minute
MATERIAL / THICKNESS	Galvanize DX51D+Z / 0.25mm-0.50mm
MATERIAL / THICKNESS	Stainless /0.35mm-0.50mm
Coil width	100 mm(max.)
Total electric supply	12 KW
Power cable	10x5
Unit Electric consumption	6 KW Hour
Compressed air supply	8 Bar, 100 liter / minute
Compressed air unit consumption	8 Bar, 7 liter / minute
LAYOUT	17 meter x 3 meter x 3 meter



PLASTER STOP		
Interior plastic thickness D	10mm den -19mm'ye kadar	Customer request
Window size (SWXLWXS)	14mm X 28mm X 1.50mm (std)	Customer request
Length (mm) L	55 mm-65 mm (std)	Customer request
Material	Galvaniz (std)	Customer request
Material thickness (mm)	0.35mm (std)	Customer request



D: 10mm - 13mm -
16mm - 19mm

Aciergalvanise
Acier inoxydable 304 L

ARCHITRAVE BEADS		
Interior plastic thickness (mm) D	13	Customer request
Width (mm) W	13-16-20-25	Customer request
Window size (SWXLWXS)	14 mm X 28mm X 1.50mm (std)	Customer request
Material	Galvaniz (std)	Customer request
Material thickness (mm)	0.35-0.50mm (std)	Customer request



W: 10mm - 13mm -
16mm - 19mm

D: 12

Aciergalvanise
Acier inoxydable 304 L